



The Direct Drive HVLS Fan features a design with enormous size, performance and savings. Producing a 2-3 mph breeze equivalent to a 4-7 degree reduction in perceived temperature, the Direct Drive works hard to ensure your facility reaches its full productivity potential.





### **KEY FEATURES**

Extruded aluminum black or clear anodized blades

Variable Frequency Drive with forward/reverse operation

- 8-24 feet (2.4-7.3 M) in diameter
- Wired touch screen remote
- Trouble shooting from ground level
- DC Brushless Direct Drive motor
- Fire Shut Down integration
- 45 dBA\*
- AMCA Tested CFM Numbers

## **OPTIONS**

- Mounting Extension
- Additional Powder Coating Options
- NEMA 4X VFD Enclosure
- NEMA 4X Remote Enclosure
- Multi Fan Remote (2-6)
- BMS Integration
- Wireless RF Module
- Slave Remote

# BLACK SILVER

### STANDARD COLORS

Custom colors and combinations are available on frame, mount & winglets.



DIAMETER SIZES

8'(2.4M) 10'(3.0M) 12'(3.7M) 14'(4.3M) 16'(4.9M) 18'(5.5M) 20'(6.1M) 24'(7.3M)

### STANDARD CONTROL



# CONTROL OPTIONS

iFan 4.3 iFan 7.0 iFan 10.0 BMS Integration




















1612 Hutton Dr. Suite 140, Dallas, TX 75006 800.558.6960 www.kelleydocksolutions.com



4Front Engineered Solutions reserves the right to change specifications and designs without notice and without incurring obligations. 4Front Engineered Solutions products may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents. Kelley as words and logos are registered trademarks belonging to ASSA ABLOY Entrance Systems AB or other companies controlled by the same organization. All rights reserved.

<sup>\*</sup>Results of sound measurement in the field may vary due to variations in surface types, environment and conditions.